

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/076749 A1

- (51) International Patent Classification⁷: E05F 15/08, E05D 13/00
- (21) International Application Number: PCT/EP03/02305
- (22) International Filing Date: 6 March 2003 (06.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
MI2002A 000497 8 March 2002 (08.03.2002) IT
- (71) Applicant (for all designated States except US): CAMP-ISA S.R.L. [IT/IT]; Via Ruffini, 13, I-20030 Palazzolo Milanese (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): NELZI, Giampaolo [IT/IT]; Via del Carso, 20, I-22070 Appiano Gentile (IT).
- (74) Agents: COPPO, Alessandro et al.; Ing. Barzano' & Zanardo Milano S.p.A., Via Borgonuovo, 10, I-20121 Milan (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVED HYDRAULIC LIFTING SECTIONAL SECURITY DOOR



(57) Abstract: An improved hydraulic lifting sectional security door, capable of being installed at an entry space to a room, comprising a pair of profiles (PRF) near each frame (STP) of the entry space, a series of panels (PNL) articulated together and a device or group (GP) for lifting the panels (PNL), which includes a hydraulic cylinder (CI), to which fixed and mobile lifting pulleys (PL1, PL2, PL3, PL4) are fixed; according to the invention the lifting cables (FA1, FA2) start from stops (FE1, FE2), which are preferably next to the cylinder (CI) and their exit in the direction of the return pulleys (PU1, PU2) takes place in a balanced manner, on the two outer sides of the lifting pulleys (PL1, PL2, PL3, PL4), so as to be able to obtain a reversible container (CAS), which allows the hydraulic cylinder (CI) and the exit of the hydraulic tube (TU) to the right or left of the entry space, according to the user's desires and requirements.

WO 03/076749 A1